



<b>Product:</b>	Iron-Horse	<b>Standard widths with borders:</b>	85 cm, 115 cm and 150 cm Black Pearl, Black Steel, Black Cedar, Granite and Midnight Grey up to 200 cm
<b>Product details:</b>	<ul style="list-style-type: none"> <li>» Extraordinary dirt catching performance</li> <li>» Skid resistant rubber back</li> <li>» Light- and colour resistant</li> <li>» PVC-free</li> <li>» Suitable for underfloor heating</li> <li>» 5 years Manufacturers Guarantee*</li> <li>» 11 years warranty against significant colour loss</li> <li>» Made in Europe</li> </ul>	<b>Standard widths without borders:</b>	3 cm smaller than for mats with borders (e.g. 82 cm)
<b>Burning behaviour:</b>	EN 13501-1 / CfI-s1	<b>Standard lengths:</b>	all lengths up to 400 cm
<b>Static electrical propensity:</b>	EN 14041 Antistatic	<b>Bespoke lengths:</b>	up to 700 cm
<b>Slip resistance:</b>	NFSI High-Traction	<b>Colouration:</b>	Solution dyed
<b>Total mat weight:</b>	2.40 kg/sqm	<b>Pile:</b>	100 % High-Twist Nylon (HTN) Polyamide 6
<b>Overall height:</b>	approx. 11 - 12 mm	<b>Pile height:</b>	approx. 10 - 11 mm
<b>Dirt absorption:</b>	800 g/sqm	<b>Pile weight:</b>	without substrate: 600 g/sqm with substrate: 700 g/sqm
<b>Moisture absorption:</b>	3 - 4 l/sqm	<b>Backing:</b>	100 % Nitrile rubber Available with kleeled or smooth backing
<b>Application areas:</b>	<ul style="list-style-type: none"> <li>» Entrances</li> <li>» Hallways</li> <li>» Elevators</li> <li>» Receptions</li> <li>» Restrooms</li> </ul>	<b>Rubber thickness:</b>	1.40 mm
		<b>Rubber weight:</b>	1.70 kg/sqm
		<b>Border width:</b>	20 mm
		<b>Border thickness:</b>	Available with or without borders 2.40 mm
		<b>Cleaning:</b>	» Washable up to 60 °C » Tumble dry up to 60 °C

## Colours:

