

ALL-IN-ONE hand washing and drying set



Description

The ALL-IN-ONE hand washing and drying set integrates the automatic water and soap tap and the automatic hand dryer into a single system, providing a hygienic, efficient and visually integrated solution for professional bathrooms.

Designed for installation in the sink or countertop, this system was developed to prevent splashing, optimise space and reduce the time spent in the washing area, improving user experience and space organisation.

The hand dryer body is **manufactured from AISI 304 stainless steel with a thickness of 1.5 mm**, ensuring high resistance and durability in intensive-use environments. The taps are **made of chrome-plated**

Features

Marca

Categoria **3in1 Dryer +
Faucet +
Dispenser**

Price

Upon request

Product in Store

[ALL-IN-ONE hand washing and drying set](#)

brass with a glossy finish. The set is also available in PVD finishes, including Bronze, Copper and Gold, allowing aesthetic adaptation to different design concepts.

Operation is completely touchless, using infrared sensors, ensuring high hygiene standards. The ALL-IN-ONE system is designed so that all residual water is directed into the sink, contributing to a cleaner, safer and more functional space.

For installation, the sink must have a minimum depth of 120 mm, with vertical walls and edges that are not excessively rounded to prevent splashing. The distance between the dryer tap and the water tap must be at least 140 mm.

Automatic hand dryer

Fast drying in 10 to 15 seconds, with a powerful air jet and adjustable speed, up to 400 km/h.

IP23 protection class, Class I electrical insulation and low standby consumption.

- Technical specifications:
 - Power supply: 220 to 240 V, 50/60 Hz;
 - Total power: 420 to 1,500 W;
 - Standby consumption: 0.3 W;
 - Noise level (at 2 m): 67 to 72 dBA;
 - Dimensions: 330 x 213 x 170 mm;
 - Optional: HEPA filter, Ion Hygienic and air freshener tablet.

Automatic water and soap tap

The automatic tap integrates water and soap dispensing

into a single point, manufactured in chrome-plated brass with a glossy finish. The sensor located on the upper right side is responsible for dispensing soap, while the sensor positioned above the water outlet activates the water flow. This system contributes to intuitive, hygienic and efficient use.

- Technical specifications:
 - Power supply: 220 to 240 V adapter or 4 AA 1.5 V batteries;
 - Soap reservoir: 1.5 L;
 - Adjustable soap dose: from 0.5 to 2 ml.

Documents

[Technical Data Sheets - EN \(192.49 Kb\)](#)

[Technical Data Sheets - ES \(605.98 Kb\)](#)

[Certificates - 1 \(391.1 Kb\)](#)

[Certificates - 2 \(48.04 Kb\)](#)

[Certificates - 3 \(62.72 Kb\)](#)