



Description

- Hand dryer operated manually by timed button.
- Surface-mounted model.
- Stainless steel sheet casing with satin finish.
- Suitable for communities and places with high frequency of use.
- Suitable for uninterrupted use. High quality components.
- Robust, vandal-proof and safe, as it is constructed without sharp edges or other dangerous elements.
- Complies with European safety directives (CE).
- With safety thermal limiter and automatic stop in case of vandalism.
- Material: AISI 304 stainless steel
- Finish: Satin
- Thickness: 1.2 mm
- Air outlet temperature: at an ambient temperature of 20°C, T°: 53°C at 10 cm
- Motor type: Universal
- Motor speed: 6500 rpm
- Air speed: 117 km/h
- Air flow rate: 5500 l/min
- Total power: 2450 W
- Motor power: 250 W
- Voltage/frequency: 220-240 V - 50/60 Hz
- Electrical insulation: Class I
- Adjustable push button time: 10-90 seconds
- Consumption: maximum 10.6 A
- Sound level at 2 meters: 70 dBA
- Projection protection rating: IPX1
- Dimensions: 240 height x 265 width x 210 depth (mm)
- Total net weight: 5.5 kg
- Electrical motor protection: Fuse
- Electrical resistance protection: Internal thermostat
- Estimated drying time: 28 seconds

Category

Product [Push Button Hand Dryer Satin
Finished Stainless Steel](#)

Brand

Category Hand Dryers

Features

Documents

[Technical Data Sheets - ES \(152.44 Kb\)](#)

[Technical Data Sheets - PT \(153.19 Kb\)](#)