



## Description

- Green polypropylene eyepiece.
- Emergency eyewash equipment.
- Instant automatic opening.
- Suitable for industries, workshops, laboratories and generally where there is a risk of fire, acid reagents, petroleum products, radioactive materials or other agents.
- Made of galvanized steel with an epoxy coating.
- Minimum pressure water supply 1.5 bar
- Maximum 5 bar.
- Water flow rate: 14 l/min  $\pm$  10%.
- Water inlet: 1/2 thread.
- Water outlet: 1+1/4 thread.
- Stainless steel spout possible, please contact us.

BOCCHI emergency showers and eyewashes fully comply with the specifications requirements of the regulations:

- EN 15154-1 Standards for shower devices for the body connected to the water network and according to which the minimum flow rate of the sprayer must be at least 100 l / min. Emergency showers DILUVIO a flow rate of more than 120 l / min at 0.3 MPa.
- EN 15154-2 Standards for eyewash units connected to the water mains and according to which the minimum flow rate of the eyewash must be at least 6 l / min. DILUVIO eye drops have a flow rate of over 14 l/min at 0.3 MPa.
- UNI9608 regulations governing the use of emergency showers and eyewashes
- UNI10271 Regulations governing the use of eyewash / laptop washers
- UNI7546 / 2 UNI7546 / 3 UNI7546 / 4 which requires the presence of an individual captive cartel for the shower and another for the emergency eyewash.
- Din 12899 PART 2
- ANSI Z358.1-2004 (American National Sanitation Institute).

## Category

---

Product [Eyewasher Polypropylene Bowl](#)

Brand

Category Portable washer eyes

## Documents

---

[Technical Data Sheets - ES\(634.1 Kb\)](#)