



Description

- Equipment Emergency eyewash pedestal high flow at low pressure with valve full bore, instant automatic manual opening and closing.
- Controlled by a lateral opening lever.
- Suitable for industries, workshops, laboratories and generally where there is risk to personnel from fire damage, acid reagents, petroleum products, radioactive materials or any other contaminant.
- Picker eyewash green polypropylene.
- Suppliers eyewash green polypropylene.
- Built in galvanized steel coated with epoxy paint.
- Brass Connectors.
- minimum supply pressure 1.5 bar water - up to 5 bar.
- Water inlet: Thread 1/2 "
- Water outlet: 1 + thread 1/4 "

BOCCHI emergency showers, they satisfy the specifications required by the regulations:

- EN 15154-1 Standards for shower devices for the body connected to the water network and according to which the minimum flow of the sprayer
- must be at least 100 l / min. Emergency showers DILUVIO a flow rate of more than 120 l / min at 0.3 MPa.
- EN 15154-2 Standards for eyewash units connected to the water mains and according to which the minimum flow rate of the eyewash must be at least 6 l / min. DILUVIO eye drops have a flow rate of over 14 l/min at 0.3 MPa.
- UNI9608 regulations governing the use of showers and eyewashes
- Emergency
- UNI10271 Regulations governing the use of eyewash / laptop washers
- UNI7546 / 2 UNI7546 / 3 UNI7546 / 4 which requires the presence of an individual captive cartel for the shower and another for the emergency eyewash.
- Din 12899 PART 2
- ANSI Z358.1-2004 (American National Sanitation Institute).

Category

Product [Emergency Eye, Green Pp Bowl 410](#)
Brand
Category Portable washer eyes

Documents

[Technical Data Sheets - ES\(120.82 Kb\)](#)
[Installation Guide - PT\(99.49 Kb\)](#)