



Description

- Team shower and emergency eyewash pedestal high flow at low pressure with valve full bore, instant automatic manual opening and closing.
- Controlled by a lateral opening lever.
- Suitable for industries, workshops, laboratories and generally where there is risk to personnel from fire damage, acid reagents, petroleum products, radioactive materials or any other contaminant.
- Body made of galvanized steel coated with epoxy paint.
- Picker eye wash stainless steel.
- Suppliers eye wash stainless steel.
- water supply pressure between 1.5 and 5 bar.
- supply temperature between 15 ° and 35 °.
- Flow: 14 l / min \pm 10%.
- Water inlet: screw 1-1/4
- Water outlet: screw 1-1/4

BOCCHI emergency showers, they satisfy the specifications required by the regulations:

- EN 15154-1. The respective standards for shower devices connected to the water system.
- EN15154-2. Respective standards for connected eye wash units to the water network.
- UNI9608, UNI10271 and DIN 12899 PART 2. Regulatory standards for eye-wash units and emergency showers.
- ANSI Z358.1-2004 (American National Standard Institute) regulatory standard of eyewash units and emergency showers.
- According to regulations the minimum eyewash flow should be 6 liters /minute and the emergency shower of 100 liters / minute: DILUVIO eye-wash flow more than 14 l/min and showers flow more than 120 l/min at 0,3 MPa.

Category

Product [Emergency Shower and Eye Wash
700](#)

Brand

Category Emergency shower

Documents

[Technical Data Sheets - ES\(89.16 Kb\)](#)
[Installation Guide - PT\(100.04 Kb\)](#)