



Description

SC700x manual emergency shower with pedestal. Full bore valve, instant automatic manual opening, closes manually.

Suitable for industries, workshops, laboratories and generally where there is a risk of fire, acids, reagents, petroleum products, radioactive materials or any other agent.

Features:

- Product material: stainless steel
- Finish: stainless steel
- Height (mm): 2150
- Width (mm): 762
- Depth (mm): 762
- Retraction diameter (mm): 300
- Flow rate: 120 L / MIN Shower AND 14 L / MIN Eye Wash
- Inlet valve: Inlet 1 1/4" g, female thread
- Outlet valve: Outlet 1 1/4" g, female thread

BOCCHI emergency showers and eyewashes fully comply with the specifications requirements of the regulations:

- EN 15154-1 Standards for shower devices for the body connected to the water network and according to which the minimum flow rate of the sprayer Must be at least 100 l / min. Emergency showers DILUVIO a flow rate greater than 120 l / min at 0.3 MPa.
- EN 15154-2 Standards for eyewash units connected to the water mains and according to which the minimum flow rate of the eyewash must be at least 6 l / min. DILUVIO eye drops have a flow rate of over 14 l/min at 0.3 MPa.
- UNI9608 regulations governing the use of emergency showers and eyewashes
- UNI10271 Regulations governing the use of eyewash / laptop washers
- UNI7546 / 2 UNI7546 / 3 UNI7546 / 4 which requires the presence of an individual captive cart for the shower and another for the emergency eyewash.
- Din 12899 PART 2

- ANSI Z358.1-2004 (American National Sanitation Institute).

Category

Product [SC700X Emergency Shower and Eye Wash](#)

Brand

Category Emergency shower