



## Description

---

- Product material: Painted steel
- Finish: Epoxy green ral6029 / stainless steel
- Height (mm): 2150
- Width (mm): 920
- Depth: 946
- Flow rate: 120l / MIN
- Inlet valve: 1" g inlet, female thread

BOCCHI emergency showers and eyewashes fully meet the specifications requirements of the regulations:

- EN 15154-1 Standards for shower devices for the body connected to the water mains and according to which the minimum flow of the sprayer Must be at least 100 l / min. Emergency showers DILUVIO a flow rate greater than 120 l / min at 0.3 MPa.
- EN 15154-2 Standards for eyewash units connected to the water mains and according to which the minimum flow rate of the eyewash must be at least 6 l / min. DILUVIO eye drops have a flow rate of over 14 l/min at 0.3 MPa.
- UNI9608 regulations governing the use of emergency showers and eyewashes
- UNI10271 Regulations governing the use of eyewash / laptop washers
- UNI7546 / 2 UNI7546 / 3 UNI7546 / 4 which requires the presence of an individual captive cartel for the shower and another for the emergency eyewash.
- Din 12899 PART 2
- ANSI Z358.1-2004 (American National Sanitation Institute).

## Category

---

Product [SCP800 Emergency Shower Platform](#)

Brand

Category Emergency shower

## Documents

---

[Technical Data Sheets - ES\(212.08 Kb\)](#)