



Description

Automatic stainless steel tap with hot and cold water mixer for countertop installation. The tap is activated by an infrared sensor built into it and is powered by 4 AA batteries that supply 6V or can be connected to the mains via a transformer (220V 50/60 hz) sold separately, please contact us.

- Activated by infrared sensor. Detection range of 12 to 18 cm.
- Chrome-plated brass body CW617N in accordance with EN248.
- Standby consumption: <0.5 mW
- Working pressure: 0.5 - 6 bar.
- Working temperature: 1 - 80C.
- Maximum recommended temperature 60C.
- Includes plastic particle filter.
- POM plastic components.
- Includes filter and all installation accessories.
- Fixed spout with replaceable M24 aerator.
- Flow rate of 6L / min with 3 bar dynamic pressure.
- Dimensions: 159 mm high x 69 mm wide x 133 mm deep.

Maintenance: use water and pH-neutral soap for cleaning, then wipe dry with a clean cloth. When cleaning the bathroom with aggressive products, the soap dish should be protected from splashes.

CE. Complies with the European Electrical Safety Directive 2014/35/EU, Electromagnetic Compatibility Directive EMC 2014/30/EU and Construction Products Directive 305/2011/EU in accordance with standards EN817:2008 and EN 15091:2013.

For more information, see the technical data sheet.

Category

Product [Automatic Tap with Mixer Batteries or Electricity](#)

Brand

Category Automatic Taps

Documents

[Technical Data Sheets - PT\(168.01 Kb\)](#)