



Description

- Electric water heater with a capacity of 120 liters
- Tripositional (vertical, horizontal wall-hung with inlet/outlet pipes on the right or inlet/outlet pipes on the left)
- Reinforced insulation
- High energy efficiency
- Class C
- Shielded heater under cover that can be replaced without having to empty the thermos
- External temperature control on the front of the manhole cover
- Vitrified boiler
- Electronic magnesium anode
- Operating pilot
- Safety valve set at 10 bar supplied with the appliance
- Total guarantee: 2 years.
- Boiler warranty: 5 years
- Internal carbon steel tank.
- External body made of carbon steel sheet coated with white epoxy-polyester paint
- Top and bottom cover of external body made of ABS
- Suitable protection against corrosion.
- Voltage: 220-240V
- Frequency: 50/60 Hz
- Maximum current: 8.7 A
- Total power: 1000w + 1000 W.
- Electrical insulation: Class I
- Product dimensions: 465x450x1123 (WxHxH) mm
- Weight: 35.55 kg
- Protection rating: IP24
- Consumption profile: M
- Annual electricity consumption: 1406 kWh / year
- Daily electricity consumption: 6.57 kWh / day

Category

Product [Tripositional 120L water heater](#)

Brand

Category Water heaters

Documents

[Technical Data Sheets - ES\(278.72 Kb\)](#)