



Description

- Emergency eyewash with foot pedal.
- Operation: Manual side lever and foot pedal.
- Material: Galvanized steel, brass fittings, stainless steel sink.
- Finish: RAL 6029 green epoxy paint.
- High-flow, low-pressure emergency eyewash with full-flow valve, instant automatic opening and manual closing by side lever and foot pedal.
- Suitable for industries, workshops, laboratories and in general where there is a risk of injury to personnel due to fire, acids, reagents, petroleum products, radioactive materials or any other contaminant.
- In accordance with European directive 93/42/EEC.
- Stainless steel eye washers.
- Brass connection parts.
- Water supply pressure: Minimum 1.5 bar - Maximum 5 bar.
- Flow rate: 14l/min \pm 10%.
- Water inlet with 1/2" thread
- Water outlet with 1+1/4" thread
- Dimensions: 102 x 26 cm (Height x Diameter)

BOCCHI emergency showers and eyewashes fully comply with the specifications requirements of the regulations:

- EN 15154-1 Standards for shower devices for the body connected to the water network and according to which the minimum flow rate of the sprayer Must be at least 100 l / min. Emergency showers DILUVIO a flow rate greater than 120 l / min at 0.3 MPa.
- EN 15154-2 Standards for eyewash units connected to the water mains and according to which the minimum flow rate of the eyewash must be at least 6 l / min. DILUVIO eye drops have a flow rate of over 14 l/min at 0.3 MPa.
- UNI9608 regulations governing the use of showers and eyewashes
- Emergency
- UNI10271 Regulations governing the use of eyewash / laptop washers
- UNI7546 / 2 UNI7546 / 3 UNI7546 / 4 which requires the presence of an individual captive cartel for the shower and another for the emergency eyewash.

- Din 12899 PART 2
- ANSI Z358.1-2004 (American National Sanitation Institute).

Category

Product [380SS Stainless Steel Pedal
Emergency Eyewash](#)

Brand

Category Portable washer eyes

Documents

[Technical Data Sheets - ES\(116.76 Kb\)](#)
[Certificates - CE\(288.5 Kb\)](#)